



YOGURT & SOFT ICE CREAM MACHINE





Compact Design
Can be installed in small places.



Low noise & vibration
Operating sound is very low compared to the same grades.



Single Flavor

Two Flavors & One Twist

	SSI-141TG	SSI-143S
Dimension	397x680x710(mm) 15.7x26.8x30.0(inch)	510x698x1,508(mm) 20.1x27.5x59.4(inch)
Weight	82Kg(181lbs)	170Kg(375lbs)
Electric	115V/60Hz/1Ph 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph	- 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph



SSI-141TG

SSI-143S



Powerful Production Capacity
Oversized compressor costs down production time.



Mass Storage Capacity
The Large Mix Hopper & Cylinder can serve Soft Ice Cream & Yogurt continuously.



(P)*Model has Air Pump System
Air Pump makes Soft Serve much smoother and softer.

Single Flavor

Two Flavors & One Twist

	SSI-300T(P)*	SSI-303S(P)*
Dimension	460x864x907(mm) 18.2x34.1x35.7(inch)	669x961x1,540(mm) 26.4x37.9x60.7(inch)
Weight	130Kg(287lbs)	330Kg(728lbs)
Electric	208~230V/60Hz/1Ph 220~240V/50Hz/1Ph	208~230V/60Hz/1Ph 220~240V/50Hz/1Ph 380~440V/50Hz/3Ph



SSI-300T(P)*

SSI-303S(P)*



Luxurious & Simple Design
Touch screen button and simplified display match with any interior design.



Artificial Intelligence Control System
AI Control System makes high quality soft serve ice cream.



- Touch Screen Button Display
- Voice Guide Function
- Smart Control System

Single Flavor

Two Flavors & One Twist

	SSI-151TG	SSI-203S
Dimension	397x814x771(mm) 15.7x32.1x30.4(inch)	580x900x1,520(mm) 22.9x35.5x59.9(inch)
Weight	90Kg(198.4lbs)	250Kg(551.2lbs)
Electric	115V/60Hz/1Ph 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph	- 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph



SSI-151TG

SSI-203S



Multipurpose ALL IN ONE
Slush & Soft Ice Cream machines are combined.
You can enjoy Slush & Yogurt together.



ALL IN ONE

Dimension	825x724x1,500(mm)	32.5x28.5x59.1(inch)
Weight	180Kg(397lbs)	
Electric	208~230V/60Hz/1Ph	220~240V/50Hz/1Ph



&



SSM-280

SSI-151TG



All IN ONE

Model Information



ALL IN ONE

Soft Ice Cream Part : Same as SSI-151TG
Slush Part

Mix Tank Capacity	9liter (2.38gallon)
Power Consumption	1,020W
Gear Motor	67Wx2EA
First Dispensing Time	30~50min
Dispensing Capacity	50cups/h
Controlled by	Torque & TC
Compressor	0.85HP(R404A)



SSI-141TG

Mix Hopper Capacity	10liter (2.64gallon)
Cylinder Capacity	1.4liter (0.37gallon)
Power Consumption	1,150W
Dasher Motor	0.37KW
Maximum Production	12Kg/h(26.5lbs/h)
First Dispensing Time	6~8min
Consecutive Dispensing	5~6cups(100cc/3.5oz)
Compressor-Cylinder	0.85HP(R404A)
Compressor-Mix Hopper	None



SSI-143S

Mix Hopper Capacity	5.5liter (1.45gallon)x2EA
Cylinder Capacity	1.4liter (0.37gallon)x2EA
Power Consumption	2,700W
Dasher Motor	0.37KWx2EA
Maximum Production	24Kg/h(52.9lbs/h)
First Dispensing Time	6~8min
Consecutive Dispensing	10~15cups(100cc/3.5oz)
Compressor-Cylinder	0.85HPx2EA(R404A)
Compressor-Mix Hopper	0.35HP(R134a)



SSI-151TG

Mix Hopper Capacity	10liter (2.64gallon)
Cylinder Capacity	1.4liter (0.37gallon)
Power Consumption	1,400W
Dasher Motor	0.37KW
Maximum Production	16Kg/h(35.3lbs/h)
First Dispensing Time	6~9min
Consecutive Dispensing	5~6cups(100cc/3.5oz)
Compressor-Cylinder	0.85HP(R404A)
Compressor-Mix Hopper	0.35HP(R134a)



SSI-203S

Mix Hopper Capacity	10liter (2.64gallon)x2EA
Cylinder Capacity	2.7liter (0.72gallon)x2EA
Power Consumption	4,500W
Dasher Motor	0.75KWx2EA
Maximum Production	42Kg/h(92.6lbs/h)
First Dispensing Time	7~11min
Consecutive Dispensing	16~40cups(100cc/3.5oz)
Compressor-Cylinder	1.3HPx2EA(R404A)
Compressor-Mix Hopper	0.35HP(R134a)



SSI-300T(P)*

Mix Hopper Capacity	17.5liter (4.62gallon)
Cylinder Capacity	3.2liter (0.85gallon)
Power Consumption	1,650W
Dasher Motor	0.75KW
Maximum Production	30Kg/h(70.5lbs/h)
First Dispensing Time	8~10min
Consecutive Dispensing	20~24cups(100cc/3.5oz)
Compressor-Cylinder	1.2HP(R404A)
Compressor-Mix Hopper	0.35HP(R134a)



SSI-303S(P)*

Mix Hopper Capacity	17.5liter (4.62gallon)x2EA
Cylinder Capacity	3.2liter (0.85gallon)x2EA
Power Consumption	7,500W
Dasher Motor	0.75KWx2EA
Maximum Production	68Kg/h(149.9lbs/h)
First Dispensing Time	8~10min
Consecutive Dispensing	50~90cups(100cc/3.5oz)
Compressor-Cylinder	2.0HPx2EA(R404A)
Compressor-Mix Hopper	0.35HP(R134a)

COMMON FACTS : Air-Cooled Condenser / Durable Stainless Steel Exterior / CE & ETL Sanitation Approved / *(P) models have Air Pump System.

*Product's exterior and specification can be modified without prior notice.



www.smoothieoperators.co.uk



JONATHAN FLEET
MANAGING DIRECTOR
P: 0845 302 4592
M: 07939 139590
F: 0845 302 4593
E: fleet@smoothieoperators.co.uk
Warwick Enterprise Park
Wellesbourne
Warwick
CV35 9EF